



25 CENTER CONSOLE



SPECIFICATIONS

LOA:25' 6" / 7.77 m
 Beam:8' 6" / 2.6 m
 Weight, dry: 5,200 lbs. / 2,359 kgs.
 Fuel capacity: 180 gal. / 681 L
 Recommended power:
 Twin Mercury 175 Verados
 Speed:.....58+ MPH
 Hull Warranty: 6 Years
 Cruise (Fuel) @ 40 MPH:..... 20 GPH
 WOT (Fuel) w/Twin 175 Verados: 58 MPH @ 36 GPH
 Maximum Cruising Range:..... 324 miles @ 90% Capacity

POWER OPTIONS

Single Mercury 275 Verado
 Twin Mercury 150 Optimax
 Twin Mercury 175 Optimax
 Twin Mercury 150 Verados
 Twin Mercury 175 Verados
 Twin Mercury 300 Verados



25 CENTER CONSOLE

STANDARD EQUIPMENT

Anchor locker w/ #13 anchor, recessed in forward bulkhead
Battery switch, explosion proof
Bilge pump, automatic (2) 1200 GPH
Center console, pre-wired w/ electronics locker, one piece plexiglass windshield, molded footrest, dry storage inside and forward facing seat
Compass
Engine, trim indicator
Fish box (2), 330 quart insulated w/ macerated overboard drain
Fuel gauge, electric
Fuel tank, heavy duty, 3/16" thick aluminum baffled; foamed, glassed, and bolted in position w/stainless steel pickup, 180 gallon capacity
Graphics, standard selection
Hand laid composite hull and deck manufactured w/multi-directional fiberglass, w/high density coring and Interplastic vinyl ester resin and w/hull and deck laminated, thru-bolted, screwed and sealed together w/heavy duty marine sealant/adhesive
Helm seat, leaning post style w/ fixed backrest and rod holders
Helm station, full instrumentation, molded foot rest, port and starboard side panel
Horn, electric
Hydraulic steering
Livewell, 38 gallon at transom
Propellers, stainless steel
Rails, bow, welded 316L stainless steel thru-bolted
Rod storage under gunwale
Rod holders, (6)
Rubrail w/ stainless steel insert
Saltwater wash down
T-Top heavy duty w/ radio box, canvas and rod holders
Trim indicators, electrical for motors and mechanical for tabs
Trim tabs, heavy-duty hydraulic, offshore hi-performance

OPTIONAL EQUIPMENT

Autopilot, TR-1 Gladiator
Backrest, Removable with Rod Holders
Canvas, Side Curtains
CE Certification Kit
Depth Gauge
Halogen Light (Additional, Front-Top Mounted)
Jumper Cable with Receptacle
Life Jacket Storage in T-Top
Outriggers
Pop-Up Bow Light
Rod Holders, Additional (2 Gunwale & 3 Transom)
Shipping Cradle
Sirius Satellite Radio
Spotlight on Bow
Swim Ladder with Bracket Mount
Tackle Box in Console



25 CENTER CONSOLE



Fountain Powerboats Performance Disclaimer

Be advised that performance figures are merely an estimate, not a guarantee, of what you can expect based on our factory testing program. The above listed speeds are verified by radar or GPS or both with one test driver and less than a forty (40) gallon fuel load. Boat speeds and range can vary depending on weight, fuel load, number of passengers, air temperature, altitude, humidity, barometric pressure, water conditions, wind, engine tuning, horsepower (HP) variance from engine to engine, propellers, and numerous other factors beyond our control. Fountain Powerboats reserves the right to make changes on standard and optional equipment at any time without prior notice. Useable fuel in a gas tank may be slightly less than the advertised fuel capacity. Speed variance can be up to 4% of the top speed.

Fountain Powerboats Options Disclaimer

Fountain Powerboats reserves the right to make changes on standard and optional equipment at any time without prior notice. Some options may have changed since the print date of this material.

Revised 2007